

TECHNICAL DATASHEET
LOCKING AND CABLING TIES in Nylon 6.6

 EN
 rev 01/2019
 p. 1/2

 Material: polyamide 6.6 (Nylon)
 Flammability UL94: class V-2
 Conforms to Directive 2002/95/EC (RoHS)

 Installation temperature: -10 °C ÷ +60 °C
 Operating temperature: -40 °C ÷ +85 °C
 Maximum temperature for short periods: +110 °C

Locking and cabling ties in polyamide 6.6, black colour

Stabilized to ultraviolet rays and weather

art.	size length x width mm	max. tightening diameter mm	strength kg
HFN1025	100x2.5	22	8
HFN1425	140x2.5	33	8
HFN2025	200x2.5	53	8
HFN1436	140x3.6	33	18
HFN2036	200x3.6	53	18
HFN2936	290x3.6	76	18
HFN3636	360x3.6	102	18
HFN2048	200x4.8	50	22
HFN2548	250x4.8	65	22
HFN2948	290x4.8	76	22
HFN3648	360x4.8	102	22
HFN3948	390x4.8	110	22
HFN4348	430x4.8	120	22
HFN5348	530x4.8	140	22
HFN2576	250x7.6	65	54
HFN3676	360x7.6	102	54
HFN4576	450x7.6	124	54
HFN5476	540x7.6	140	54
HFN7576	750x7.6	178	54
HFN7888	780x8.8	182	74
HFN5390	530x9.0	140	79
HFN10290	1020x9.0	226	79

Locking and cabling ties in polyamide 6.6, white colour

art.	size length x width mm	max. tightening diameter mm	strength kg
HFB1025	100x2.5	22	8
HFB1425	140x2.5	33	8
HFB2025	200x2.5	53	8
HFB1436	140x3.6	33	18
HFB2036	200x3.6	53	18
HFB2936	290x3.6	76	18
HFB3636	360x3.6	102	18

TECHNICAL DATASHEET
LOCKING AND CABLING TIES in Nylon 6.6

 EN
 rev 01/2019
 p. 2/2

art.	size length x width mm	max. tightening diameter mm	strength kg
HFB2048	200x4.8	50	22
HFB2548	250x4.8	65	22
HFB2948	290x4.8	76	22
HFB3648	360x4.8	102	22
HFB3948	390x4.8	110	22
HFB4348	430x4.8	120	22
HFB5348	530x4.8	140	22
HFB2576	250x7.6	65	54
HFB3676	360x7.6	102	54
HFB4576	450x7.6	124	54
HFB5576	550x7.6	143	54
HFB7576	750x7.6	178	54
HFB7888	780x8.8	182	74
HFB5390	530x9.0	140	79
HFB10290	1020x9.0	226	79

Locking and cabling ties in polyamide 6.6, green colour

art.	size length x width mm	max. tightening diameter mm	strength kg
HFV1025	100x2.5	22	8
HFV1436	140x3.6	33	18
HFV2036	200x3.6	53	18
HFV2048	200x4.8	50	22
HFV2948	290x4.8	76	22